

Acoustik TOHN



ACOUSTICAL WALL PANEL

TECHNICAL DATA

Wood Species:

White oak

Dimension:

12.8" x 96" / 8.5 sq.ft.


Thickness:

23.4 mm

Finish:

10% U.V. varnish
(low V.O.C. water based clear sealer)
Antimicrobial protection

Fire rating: Class A




LAYERS

Top:

Wood veneer
with a fire treated MDF core

Bottom:

Stone wool with a MDF frame






ACOUSTICAL PERFORMANCE

Frequency (Hz):	Absorption coefficient:
250	0.232
500	0.579
1000	0.784
2000	0.817

NRC:
0.61

SAA:
0.60

Absorption Spectrum of Tested Panels



ENVIRONMENT

Stone wool:

Up to 29% recycled content

Wood:

Responsibly sourced in North America


PART OF OUR ZERO WASTE POLICY

Varnish:

Reused and/or recycled

Wood:

We maximize our production and product development to minimize waste. Any leftover is transformed into highly efficient clean-burning wood pellets



Acoustik TOHN

finium.ca



MADE IN CANADA

DUE TO THE NATURE OF THE PRODUCT AS A UNIQUE ORGANIC MATERIAL, THERE MAY BE IMPERFECTIONS AND COLOR VARIATIONS, AND THE FINAL PRODUCT MAY DIFFER FROM THE SAMPLES.